

For Use By Qualified Personnel Only!



Danger: Extremely flammable gas. Flammable to open flame or spark. Proceed with caution if used in systems designed for non-flammable refrigerants. Flammable liquid and vapor. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Very toxic to aquatic life with long-lasting effects. DO NOT incinerate!

Precautions: Keep away from heat/hot surfaces/open flames/sparks. NO SMOKING. Keep container closed. Use ONLY non-sparking tools. Take precautionary measures against static discharge. Avoid breathing gas/dust/fumes/mist/vapors/spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear respiratory protection, cold insulating gloves, eye protection, and protective clothing. Store in a well-ventilated area. Keep cool. Protect from sunlight. Dispose of contents/container to an approved waste disposal plant.

First Aid: Inhalation: Obtain medical attention if breathing difficulty persists. Take proper precautions to ensure your own safety before attempting rescue (wear appropriate PPE, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing.

Eye contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Obtain medical attention.

Skin contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Thaw frosted parts with lukewarm water. DO NOT rub affected area. Get immediate medical advice/attention.

Ingestion: Rinse mouth. DO NOT induce vomiting. Seek medical attention.

In all cases obtain immediate medical attention.

All labeled hazard precautions must be observed. See Safety Data Sheet (SDS) for this product.



R600a Refrigerant

Net Weight 6oz (170.1g)



Directions For Use

Read and understand all warnings and directions before use. As per use with any flammable substance, take adequate precautions during use.

1. Install can tap valve and charging hose.
2. Install charging hose on low pressure side ONLY.
3. Stand can UPRIGHT to charge.
4. Fill system to correct pressure with the correct amount of refrigerant.
5. DO NOT overcharge the system.
6. Contact a licensed professional waste disposal service to dispose of this material.

NOTE: For use with self-sealing can top taps.



LEAK SAVER

Leak Saver
PO Box 151
Eola, IL 60519
888-675-6088
info@leaksavers.com
www.leaksavers.com

