

### The HVAC Guys Philosophy

We are just two HVAC Guys bringing you the same products that we use on our own jobs. We've tried virtually everything to make sure we give you the best products we use on our every day jobs. Every single client is important to us. That's why we offer a **100% SATISFACTION GUARANTEE** on all our products. For any help or questions, you can reach out to us at [info@hvaguyproducts.com](mailto:info@hvaguyproducts.com) or call us at 888-675-6088.

This aerosol adhesive features a wide web spray pattern and ranks among the top-performing aerosol adhesives on the market. Designed for both temporary and permanent bonding, its high solids formula works exceptionally well on uneven or porous surfaces, as well as heavier materials. It is specially made for materials that are subject to varying temperatures like HVAC insulation, duct liner, and duct wrap. It is waterproof, flexible, and transparent, also making it suitable for demanding adhesive tasks involving materials such as leather, cardboard, most plastics, and cloth. Importantly, this product is free from chlorinated solvents and ozone-depleting substances. Cleanup is straightforward using an adhesive remover containing petroleum distillates or the citrus-based compound d-limonene.

**Instructions for Use:** This product is intended for use by authorized HVACR professionals and should be applied according to the following guidelines:

**Preparation:** Shake the can thoroughly before each use. Avoid aiming the valve toward your face. Hold the can upright and apply the adhesive in a side-to-side motion, maintaining a distance of 8 to 12 inches from the surface. Note: This adhesive is not suitable for use on vinyl. It is not intended for bonding surfaces that exceed 122°F (50°C).

**For Temporary Bonds:** Apply the adhesive to one surface, let it become tacky, and then join the surfaces together.

**For Permanent Bonds:** Generously spray both surfaces. Allow the adhesive to become tacky and then press the surfaces together.

**Cleanup:** After completing the application, turn the can upside down and spray for two seconds to clear the valve, preventing clogs. Wipe the nozzle clean while the adhesive is still wet. For dried adhesive in the valve or on the nozzle, use an adhesive remover or replace the actuator tip. To remove overspray or unclog the nozzle, use a remover containing petroleum distillates or d-limonene.



# ThermaTack SPRAY



## Insulation Adhesive Aerosol Spray Glue For HVAC Duct Wrap

- Wide Coverage Web Spray Pattern
- Fast Tacking and Quick Adhesion
- Designed for HVACR Insulation Applications



### WARNINGS

**DANGER: KEEP OUT OF REACH OF CHILDREN. READ LABEL AND SDS BEFORE USE.**

**EXTREMELY FLAMMABLE AEROSOL.** PRESSURIZED CONTAINER. MAY BURST IF HEATED. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE DROWSINESS OR DIZZINESS. MAY CAUSE DAMAGE TO CENTRAL NERVOUS SYSTEM THROUGH PROLONGED OR REPEATED EXPOSURE VIA INHALATION. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hands and face thoroughly after handling. Wear protective gloves. Wear eye protection, if exposed or concerned. Get medical attention.

**FIRST AID: IF SWALLOWED:** Immediately call a poison center or a doctor. Do NOT induce vomiting.  
**IF ON SKIN:** Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash it before reuse.  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.  
**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.

**INGREDIENTS (C.A.S.#):** Acetone (67-64-1), Hexane (110-54-3), Propane (74-98-6), Butane (106-97-8).

**HMS RATINGS:** Health: 2; Flammability: 4; Reactivity: 0; Maximum Personal Protection: G



**Professional HVAC Products LLC**  
1309 Colson Ave., STE 1200  
Sheridan, Wyoming 82801  
Tel: 888-675-6088

[info@hvaguyproducts.com](http://info@hvaguyproducts.com)



PIN: HG-TTSA